



PILLAR DRILL MACHINE



MODEL	JPDS-13	JPDS-16	JPDG-20	JPDG-25	JPDG-32	JPDG-38
SPECIFICATIONS						
Drilling Capacity (mm)	13	16	20	25	32	38
Spindle Travels (mm)	75	75	95	120	145	190
Spindle Centre to Column (mm)	150	150	205	245	280	320
Spindle Nose to Table (Max.) (mm)	290	415	410	650	765	815
Spindle Nose to Base (Max.) (mm)	395	535	600	1015	1090	1180
Column Diameter (mm)	47	47	74	74	85	124
Morse Taper in Spindle	JT-6	MT-2	MT-2	MT-3	MT-3	MT-4
Table Size (mm)	200	200	315	350	405	495
Base Working Area (mm)	155 x 155	165 x 165	215 x 255	250 x 330	305 x 305	400 x 400
No. of Speeds	4	4	8	8	8	8
Spindle Speed (RPM)	700 - 2480	700 - 2480	90 - 3000	110 - 2540	110 - 2540	100 - 2000
V-Belt Size	A-32	A-34	A-42	B-52	B-54	B-60
Power Required (HP)	0.5	0.5	0.75	1	1.5	2

Also Available 4 Speed Models such as JPDS-20 & JPDS-25

STANDARD ACCESSORIES : Motor Pulley.

➤ We are constantly striving to improve our products and therefore reserve the right to change design, material and specifications without previous notice.

Macstar Machine Tools Pvt. Ltd.

E-Mail: del@macstarindia.com

Website: www.macstarindia.com