



ALL GEARED MILLING MACHINE



SPECIFICATIONS

Model	AGM-2	AGM-3	AGM-4
Table Size	1300 x 280 mm	1450 x 300 mm	1600 x 350 mm
Tee Slots	3 x 14 mm	3 x 16 mm	3 x 16 mm
Longitudinal Traverse	660 mm	835 mm	1015 mm
Cross Traverse	220 mm	250 mm	350 mm
Vertical Traverse	400 mm	450 mm	500 mm
Spindle Nose	ISO-40	ISO-40	ISO-40
Spindle Speeds	8(40 - 1150)	8(40 - 1150)	8(40 - 1150)
Arbor Diameter (Universal Models)	1"	1"	1"
Swing of Vertical Head to Either Side (Vertical Models)	90°	90°	90°
Table Feed (Cross & Longitudinal)	8(15 - 150)	8(15 - 150)	8(15 - 150)
Rapid Traverse	1150 mm/minute	1150 mm/minute	1150 mm/minute
Power Required for Coolant Pump	0.1 HP	0.1 HP	0.1 HP
Power Required for Feed	2 HP	3 HP	3 HP
Power Required for Spindle	2 HP	3 HP	5 HP

Available in Universal & Vertical Models.

STANDARD ACCESSORIES : Coolant Pump, Tool Kit, Electricals.

EXTRA ACCESSORIES : Vertical Attachment, Rack Cutting Attachment, Slotting Attachment, Dividing Head, Rotary Table, ISO-40 Adaptor

➤ We are constantly striving to improve our products and therefore reserve the right to change design, material and specifications without previous notice.

Macstar Machine Tools Pvt. Ltd.

E-Mail: del@macstarindia.com

Website: www.macstarindia.com